



## VIPER™ ELITE CLASSIC

4 FLAVOR FROZEN DISPENSER



## FEATURES

Building on nearly 50 years of experience, Viper Elite raises the bar in frozen with superior engineering and quality.

**Enhanced Reliability** – Increase uptime with the most reliable FCB dispenser on the market

**Syrup Flexibility** – Pressure transducers ensure you'll be able to perform as syrups change in the future

**Expand Drink Portfolios** – Individual barrel flexibility (FCB/FUB) and profile settings

**Intelligent Defrost™** – Patented adaptive defrost keeps you up and running during peak demand so you never miss a sale

**Information at your fingertips** - Quickly access manuals and easy-to-follow staff and service videos via QR code

**C3 Technology** – Cooling, carbonation, and controls provide unmatched drink profile consistency, builds repeat sales and minimizes syrup usage

**Programmable sleep mode** – Conserves energy in off hours

**Technician designed** – Reduced maintenance and service times

**ADA Compliant** – Stainless push handle valve

## MODELS

PART NUMBER	DESCRIPTION
621460142	Viper Elite Classic 4 flavor, 230/60Hz, SPH Valve, Tall Merchandiser
621460042	Viper Elite Classic 4 flavor, 230/60Hz, Motorman Valve, Tall Merchandiser
621460041	Viper Elite Classic 4 flavor, 230/60Hz, Motorman Valve, Short Merchandiser

SPH stands for Stainless Push Handle. For FUB applications, Motorman valves are recommended.

## ACCESSORIES

PART NUMBER	DESCRIPTION
629087406	Leg kit, 4" legs adjustable to 5.25"
620046556	Viper 4 flavor cart, stainless steel
620046477	Viper 4 flavor generic graphic for tall merchandiser
620047323	Viper 4 flavor generic graphic for short merchandiser
620042868	Generic flavor card set (includes 18 flavors)
325674000	Buck and boost transformer

Refer to installation accessory guideline for complete list.

## TECHNICAL SPECIFICATIONS

**ELECTRICAL RATINGS** . . . . . 230V +/- 15V 60Hz, 30a, single phase  
(includes 8ft. power cord NEMA L6-30P molded plug connection)

**PRESSURE REQUIREMENTS** . . . CO2 = 75 psig  
Water = 25 min. psig dynamic

**DRAW CAPACITY** . . . . . 75-82 oz/min. continuous, alternating barrels @ 75°F ambient

**REFRIGERATION** . . . . . 19,000 BTU, R404A

**MINIMUM CLEARANCE REQUIRED** . . . . . Top: 12"  
Each side: 2" or Back: 2"

**UNIT DIMENSIONS** . . . . . 29"W x 32.5"D x 43.7"H  
(tall merchandiser)  
29"W x 32.5"D x 37"H  
(short merchandiser)

**GRAPHIC CARD DIMENSIONS** . . . 28.75"W x 18.75"H  
(tall merchandiser)  
28.75"W x 11.79"H  
(short merchandiser)

**FLAVOR CARD DIMENSIONS** . . . 6.5"W x 4"H

**SHIPPING WEIGHT** . . . . . 500 lbs; cart 200 lbs

**AGENCY LISTINGS** . . . . .  

