

INSTALLATION INSTRUCTIONS

EXTENDED SPLASH PANEL KIT

SAFETY INSTRUCTIONS

 **WARNING:**

Before starting installation, read and understand all safety label and warnings on the machine. Also review and understand all safety instructions in the owners, installation and service manuals.

Failure to comply could result in serious injury, death or damage to the equipment.

QUALIFIED SERVICE PERSONNEL

 **WARNING:**

Only trained and certified electrical, plumbing and refrigeration technicians should service this unit.

All wiring and plumbing must conform to national and local codes. Failure to comply could result in serious injury, death or equipment damage.

SAFETY PRECAUTIONS

This unit has been specifically designed to provide protection against personal injury. To ensure continued protection observe the following:

 **WARNING:**

Disconnect power to the unit before servicing. Follow all lock out/tag out procedures established by the user. Verify all power is off to the unit before performing any work.

Failure to comply could result in serious injury, death or damage to the equipment.

 **CAUTION:**

Always be sure to keep area around the unit clean and free of clutter.

Failure to keep this area clean may result in injury or equipment damage.

INSTRUCTIONS FOR USE ON A QUEST UNIT WITH DRAIN TUBE HOLES IN THE BASE

1. Remove the drip tray and screws holding the splash panel (as shown).



Figure 1

2. Remove the screws securing the drip tray support arms (as show).



Figure 2

3. Place bracket 720500072 (QST 2) under unit, align with rivnut holes and secure in place with threaded leg.



Figure 3

4. Replace the drip tray arms in the bracket. The holes are threaded for the 8-32 screws.



Figure 4

5. Attach the new drain and overflow tubes (as shown).



Figure 5

6. Mount the extended splash panel (as shown) and replace the drip tray.



Figure 6

INSTRUCTIONS FOR USE ON A QUEST UNIT WITHOUT DRAIN TUBE HOLES IN THE BASE.

1. This is the view of the frame without the drain tube holes.



Figure 7

2. Attach the tank drain fitting (400104) and tube and rotate it. The tank drain tube should be trimmed (as shown)



Figure 8

3. Remove cabinet drain barb and insert the t-fitting (396108000). The tube from the tank drain is attached (as shown).



Figure 9

4. The tube is flexible enough to be squeezed between the frame and splash panel without restricting the water drainage.



Figure 10

5. The longer screws included (0704105) are to allow easier assembly of the splash panel with the drain tube behind it.



Figure 11