

INSTALLATION INSTRUCTIONS

Millennium Base Key lock Kit (P/N 629087548)

SAFETY INSTRUCTIONS

 **WARNING:**

Before starting installation, read and understand all safety label and warnings on the machine. Also review and understand all safety instructions in the owners, installation and service manuals.

Failure to comply could result in serious injury, death or damage to the equipment.

QUALIFIED SERVICE PERSONNEL

 **WARNING:**

Only trained and certified electrical, plumbing and refrigeration technicians should service this unit.

All wiring and plumbing must conform to national and local codes. Failure to comply could result in serious injury, death or equipment damage.

SAFETY PRECAUTIONS

This unit has been specifically designed to provide protection against personal injury. To ensure continued protection observe the following:

 **WARNING:**

Disconnect power to the unit before servicing. Follow all lock out/tag out procedures established by the user. Verify all power is off to the unit before performing any work.

Failure to comply could result in serious injury, death or damage to the equipment.

 **CAUTION:**

Always be sure to keep area around the unit clean and free of clutter.

Failure to keep this area clean may result in injury or equipment damage.

INSTALLATION INSTRUCTIONS

This instruction applies to Millennium 2 Models for converting top panel key lock operation to a key lock mounted into the dispenser base.

Replacement Parts List	
Part Number	Description
620316408	Wire Harness
33300	Key lock (Includes Key)

1. Unplug the unit from electrical power.
2. Disassemble Merchandiser, Drip Tray, Splash Plate as needed and disconnect existing Key lock connector from the Transformer Harness.



Figure 1.

3. Install the Key lock included in this kit into the hole on either the left or the right side of the Base. Tighten the Key lock nut securely.



Figure 2.

4. Install the Wire Harness included with this kit onto the new Key lock terminals and onto the Transformer harness. Route Wire Harness to avoid interference with internal components.



Figure 3.

5. Remove the old Key lock. Re-assemble Splash Plate, Drip Tray, etc.



Figure 4.

6. Operate dispenser, check for proper operation of the new Key lock.