



INSTALLATION INSTRUCTIONS

ED 150 DISPENSE LEVER/SWITCH REPLACEMENT

Tools Required:

Phillips Screwdriver

1/2-in. Wrench or adjustable (Crescent) Wrench

- 1. Disconnect power from unit.
- 2. Remove splash panel to access dispense switch.
- 3. Remove screws attaching ice dispense lever retaining bracket to beverage panel.
- 4. Remove ice dispense lever from beverage panel.
- 5. Remove switch boot (1/2-in. wrench) and dispense switch from beverage panel.
- Disconnect wires from old dispense switch.
- 7. Connect black wire to COMMON terminal of new dispense switch.
- 8. Connect red wire to NORM OPEN terminal of new dispense switch.
- 9. Install spacer onto the threaded bushing of dispense switch before mounting switch to beverage panel with new switch boot. (Spacer fits between beverage panel and dispense switch.)
- 10. Assemble new ice dispense lever to beverage panel using retaining plate provided and two screws; orient retaining bracket as shown.
- 11. Replace splash panel and mounting screws.
- 12. Reconnect power to unit.
- 13. Verify proper operation of the new dispense lever and switch.
- 14. Return old parts to: IMI Cornelius

One Cornelius Place Anoka, MN 55303-6234 Attention: Rob Foster

