

Quest Elite 2000W

2-Flavor Post-Mix Dispenser with Water Button

Specification Sheet





Features

Dedicated Water Line

Dispense water without the need to remove a primary product

Enhanced Door Gasket

Engineered for superior sealing to lock in cool air and block out heat, ensuring optimal temperature control

Innovative Magnetic Latch

Ensures precise alignment, preventing doors from being left ajar and maintaining consistent temperatures

Wide Product/Ratio Capability

Dispense juices and lemonades with pulp, teas, plus cold coffees within a 3:1 to 8:1 ratio

Patented Mixing System

Consistent quality drinks with no stratification, slugging, or dripping

Frost-free Refrigeration

Safely accommodate frozen, ambient, or aseptic concentrate BIBs and cartridges

Large Ice Bank

Six to eight-pound cooling capacity ensures cold drinks during peak demand

Optional Touchless Dispense Kit

Hygienic, touch-free dispense coversion kit available

LED Illuminated Graphic

Attract attention while reducing energy and maintenance cost with theye-catching backlit merchandiser

'Sold Out' Indicator

Prevent missed sales with product-out alerts







Quest Elite 2000W

2-Flavor Post-Mix Dispenser with Water Button

Specification Sheet





Technical Specifications

Electrical	115V/60Hz, 230V/50Hz
Refrigerant	R290 refrigerant (56g) hermetically sealed
Ice Bank Size	6-8 lbs.
Operating Conditions	40oF to 100oF (4.4o C to 37.8oC)
Interior Cabinet Dimensions	7.5"W x 9.5"D x 9.0"H (19.5 cm x 24.1 cm x 22.9 cm)
Dispenser Dimensions	10.6"W x 25.0"D x 34.0"H (26.9 cm x 63.5 cm x 86.4 cm)
Recommended Clearance	Top: 12.0" (30.5 cm) Back: 4.0" (10.2 cm) and Sides: 4.0" (10.2 cm)
Weight	Dry: 104 lbs. (47.2 kg) Operating: 136 lbs. (61.7 kg) Shipping: 120 lbs (54.4 kg)
Merchandiser Graphic Size	Single Panel: 11.7"W x 11.1"H (29.7 cm x 28.1 cm) Multi-Panel: 2.9"W x 13.0"H (7.4 cm x 33.9 cm)

Post-Mix Ratio	3:1, 4:1, 5:1, 6:1, 7:1, 8:1
Drinks Per Minute	Three 12 oz drinks/min (355 mL) up to 100 drinks @ 750F (240C) ambient, 750F (240C) incoming water, and 410F (50C) concentrate w/o exceeding 400F (4.40C).
Concentrate Storage	2 - 3.5L bottles
Water Connection	3/8" SAE male flare fitting on dispenser
Water Supply Requirements	Optimum Pressure: 50psi (3.4 bar) flowing 3oz/sec Minimum Static Pressure: 30psi (2.1 bar) Maximum Static Pressure: 60psi (4.1 bar)
	For water pressure exceeding the optimum supply s pecification, flow control set at 50psi is recommended
Flow Rate	Beverage pour rate 1-2.2oz/sec
Agency Listing QST ELITE 2290 QST ELITE 2290 W	CUDUS NSF CE

Part Number	Description
721Q26111W	Quest Elite Water Button R290 QLT, 2 Flavor, illuminated, portion control 115V/60 single panel merchandiser
721Q26121W	Quest Elite Water Button R290 QLT, 2 Flavor, illuminated, portion control 115V/60 multi panel merchandiser
721Q26211W	Quest Elite Water Button Non Flush R290 QLT, 2 Flavor, illuminated, portion control 115V/60 single panel merchandiser
721Q26221W	Quest Elite Water Button Non Flush R290 QLT, 2 Flavor, illuminated, portion control 115V/60 multi panel merchandiser
720401107	3.5 L Refillable Concentrate Reservoir
729011126	Bag-In-Box Option Kit
729011183	Extender Nozzle Kit
729011004	Tall Cup Adapter Kit - 2 Flavor
629097998	Touchless Dispense Kit - 2 Flavor
729011218	Portion Control Kit - 2 Flavor
629097144	ADA Installation Kit - 2 Flavor

To learn more about **Quest Elite**, visit cornelius.com

